**Journal of Informatics and Mathematical Sciences** Volume 3 (2011), Number 2, pp. 107–125 © RGN Publications



# Iterative Operator Splitting Method for Coupled Problems: Transport and Electric Fields

J rgen Geiser

**Abstract.** In this article a new approach is considered for implementing operator splitting methods for transport problems, influenced by electric fields. Our motivation came to model PE-CVD (plasma-enhanced chemical vapor deposition) processes, means the flow of species to a gas-phase, which are influenced by an electric field. We consider a convection-diffusion equation and a Lorence force in the electrostatic case.

The iterative splitting schemes is given as an embedded coupling method and we apply such a scheme as a fast solver. The decomposition analysis is discussed for the nonlinear case. Numerical experiments are given with respect to explicit Adam-Bashforth schemes. We discuss the convergence behavior in time and space for the iterative schemes.

# 1. Introduction

In the field of numerical modeling and simulation of transport problems, the influence of electrical fields are of interest.

We consider a coupled model of a convection-diffusion equation with a electrostatic field.

While the underlying equations are coupled nonlinear and linear equations, we propose iterative schemes to solve such schemes.

We deal with the following model equations:

$$\frac{\partial u}{\partial t} = -\mathbf{v} \cdot \nabla u + \nabla \cdot D \nabla u, \tag{1}$$

$$\frac{\partial \mathbf{v}}{\partial t} = -\frac{\frac{\partial u}{\partial t}}{u}\mathbf{v} + \frac{v}{\mu}\mathbf{E},\tag{2}$$

$$u(\mathbf{x}, \mathbf{t_0}) = u_0(\mathbf{x}),\tag{3}$$

$$\mathbf{v}(\mathbf{x}, \mathbf{t}_0) = \mathbf{v}_0(\mathbf{x}),\tag{4}$$

2000 Mathematics Subject Classification. 35K15, 35K57, 47F05, 65M60, 65N30.

*Key words and phrases.* Numerical analysis; Iterative solver method; Adam-Bashforth methods; Nonlinear convergence.

where *u* is the density of the ion concentrations, **v** is the velocity field, **E** is the electric field and *v*,  $\mu$  are parameters. We consider Neumann boundary conditions.

The iterative splitting scheme is considered after the spatial discretization and we obtain the following nonlinear ordinary differential equation system:

$$\frac{\partial u}{\partial t} = A_1(\mathbf{v})u + B(\mathbf{v})u,\tag{5}$$

$$\frac{\partial \mathbf{v}}{\partial t} = A_2 \left( \frac{\partial u}{\partial t}, u \right) \mathbf{v} + \mathbf{f},\tag{6}$$

where  $A_1, A_2, B$  are given of the spatial discretization.  $\mathbf{f} = \frac{v}{\mu} \mathbf{E}$ .

Here we deal with a iterative scheme to solve the nonlinear equation.

## 2. Mathematical Model

We motivate our study by simulating a growth rate of a deposition process that can be done by PE-CVD (plasma enhanced chemical vapor deposition) processes, see [12] and [15]. A gas exposed to an electric field in low pressure conditions (< 5 Torr) results in a non-equilibrium plasma, see [1] and [14]. Such ionized media, known as "cold" plasma or glow discharges, are powerful surfacemodification tools in Material Science and Technology. Low-pressure plasmas allow to modify the surface chemistry and properties of materials compatible with low-medium vacuum, through a PE-CVD process, see applications [14]. Here a porous media model with permeable layers is an attractive simulation models. The transport, chemical and sorption processes in a homogeneous media can be used to simulate species transport in a plasma enhanced environment, controlled by pressure, by temperature and by additional electric fields.

We concentrate on a far-field model and assume a continuum flow, and that the transport equations can be treated with a convection-diffusion-reaction equation, due to a constant velocity field, see:

$$\frac{\partial u}{\partial t} + \nabla F u = 0, \text{ in } \Omega \times [0, t]$$

$$F = \mathbf{v} - D \nabla,$$
(7)

$$c(x,t) = c_0(x), \text{ on } \Omega, \tag{8}$$

$$\frac{\partial c(x,t)}{\partial n} = 0, \text{ on } \partial \Omega \times [0,t], \tag{9}$$

where *c* is the particle density of the ionized species. *F* the flux of the species. **v** is the flux velocity through the chamber and porous substrate which is influenced by the electric field. *D* is the diffusion matrix. The initial value is given as  $c_0$  and we assume a Neumann boundary condition.

# **Electric Field (Distribution)**

To model the influence of the electric field on the concentration we use a pointwise approach that means we assume that the concentration in a point  $\mathbf{x} \in \Omega$ behaves like a point-charge of mass  $m = \mu u$ ,  $\mu \in \mathbb{R}^+$  and charge q = vu,  $v \in \mathbb{R}$ . We also assume that there is no interaction between these point-charges. (This interaction is already considered in the convection-diffusion equation). In general the Lorentz force in this case can be written as  $\mathbf{F} = q(\mathbf{E} + v \times \mathbf{B})$ . So that the Lorentz force in our electrostatic case is given as:  $\mathbf{F} = v u \mathbf{E}$ .

We can write the equation of motion as follows:

$$\frac{\partial \mathbf{p}}{\partial t} = \mu u \mathbf{E},$$

$$\frac{\partial m}{\partial t} \mathbf{v} + m \frac{\partial \mathbf{v}}{\partial t} = v u \mathbf{E},$$

$$\frac{\partial \mathbf{v}}{\partial t} + \frac{\frac{\partial u}{\partial t}}{u} \mathbf{v} = \frac{v}{\mu} \mathbf{E}.$$
(10)

## 3. Discretization Methods

## 3.1. Discretization methods of the Convection-Diffusion equation

For the 3 dimensional convection-diffusion equation we apply a second order finite difference scheme in space and a higher order discretization scheme in time.

$$\begin{aligned} \frac{\partial u}{\partial t} &= -\mathbf{v}\nabla u + D\Delta u\\ &= -v_x \frac{\partial u}{\partial x} - v_y \frac{\partial u}{\partial y} - v_z \frac{\partial u}{\partial z} + D \frac{\partial^2 u}{\partial x^2} + D \frac{\partial^2 u}{\partial y^2} + D \frac{\partial^2 u}{\partial z^2},\\ u(\mathbf{x}, \mathbf{t_0}) &= u_0(\mathbf{x}), \end{aligned}$$

We apply dimensional splitting to our problem

$$\frac{\partial u}{\partial t} = A_x u + A_y u + A_z u$$

$$A_x = -v_x \frac{\partial u}{\partial x} + D \frac{\partial^2}{\partial x}$$

where

 $A_x = -v_x \frac{\partial u}{\partial x} + D \frac{\partial u}{\partial x^2}.$ We use a 1st order upwind scheme for  $\frac{\partial}{\partial x}$  and a 2nd order central difference scheme for  $\frac{\partial^2}{\partial x^2}$ . By introducing the artificial diffusion constant  $D_x = D - \frac{v_x \Delta x}{2}$ we achieve a 2nd order finite difference scheme

$$L_x u(x) = -v_x \frac{u(x) - u(x - \Delta x)}{\Delta x} + D_x \frac{u(x + \Delta x) - 2u(x) + u(x - \Delta x)}{\Delta x^2}$$

because the new diffusion constant eliminates the first order error (i.e. the numerical viscosity) of the Taylor expansion of the upwind scheme.  $L_v u$  and  $L_z u$ are derived in the same way.

Depending on the coefficients, the semi-discretization of the diffusion equations yields stiff or even very stiff equations, which demand for implicit methods. Nowadays, modern multigrid or multilevel methods solve linear equations in Nlog(N) operations, even direct methods can handle systems up to N = 1e + 6 (and higher) very efficiently nowadays.

Therefore, we apply for the discretization in time several explicit Runge-Kutta and Adam-Bashforth methods, means direct methods, as an alternative discretisation method to implicit schemes.

This leads to restrictions of the step-size in time but on the other hand the we can control the accuracy of the results. While we restrict us to single CPU processors, we achieved for our applications that we are more efficient in computational and memory resource with the optimization of the explicit methods as to apply a resource intensive implicit methods, e.g. implicit Runge-Kutta discretization with Multilevel method as solver.

## 3.2. Analytical solution of the Electrostatic field

Equation (10) is a linear ODE. We have to solve it at every time-step with the initial condition  $v(t^n) = v_n$ . It has the following analytical solution:

$$v(t) = v_n \frac{u_n}{u(t)} + \frac{v}{\mu} E \frac{1}{u(t)} \int_{t_n}^t u(t) dt.$$
 (11)

Under the assumption of constant coefficients (that means it holds  $u(t) = u(t_n) = u_n \forall t \in [t_n, t_{n+1}), \dot{u}(t) = \dot{u}(t_n) = \dot{u}_n \forall t \in [t_n, t_{n+1})$ ) we get a solution that is absolutely explicit:

$$v(t) = \left(v_n - \frac{vu_n}{\mu \dot{u}_n}E\right) \exp\left(-\frac{\dot{u}_n}{u_n}t\right) + \frac{vu_n}{\mu \dot{u}_n}E.$$
(12)

**Remark 1.** The analytical solution is only given for theoretical analysis, for practical computations, we have to derive a numerical scheme. The schemes are discussed in the following parts.

## Iterative computation of the electrostatic field

We apply successive approximation to the computation of the electrostatic field:

$$v_{i}(t) = v_{n} \frac{u_{n}}{u_{i-1}(t)} + \frac{v}{\mu} E \frac{1}{u_{i-1}(t)} \int_{t_{n}}^{t} u_{i-1}(t) dt, \text{ for } i = 1, 2, 3, \dots, t \in [t^{n}, t^{n+1}],$$
(13)

where we assume  $u_{i-1}(t)$  is given from previous computations and  $v_i(t^n) = v(t^n)$ . The stopping criterion is given as:

$$\|v_i(t) - v_{i-1}(t)\| = err_1, \ \|u_i(t) - u_{i-1}(t)\| = err_2, \ \max\{err_1, err_2\} \le err,$$
 (14)

where err is a given error-bound.

The integral in (13) is computed as:

(1) Trapezoidal rule:

$$\int_{t_n}^t u_{i-1}(s)ds \approx \frac{1}{2}(t-t^n)(u_{i-1}(t)+u_{i-1}(t^n)), \qquad (15)$$

where we obtain a second order scheme.

(2) Taylor expansion around  $t^n$ 

$$\int_{t_n}^t u_{i-1}(s)ds \approx (t-t_n)u_{i-1}(t^n) + \frac{1}{2}(t-t^n)\frac{du_{i-1}}{dt}(t^n), \qquad (16)$$

where we have a also a second order scheme and  $\frac{du_{i-1}}{dt}(t^n)$  is given as:

$$\frac{du_{i-1}}{dt}(t^n) = Au_{i-1}(t^n) + Bu_{i-1}(t^n).$$
(17)

**Remark 2.** We assume to have sufficient smoothness of the solution  $u_{i-1}$ . Further the computation of the derivation is given with the matrix operators.

# 3.3. Apriori error estimates: CFL Conditions

In the following we describe the error estimates:

**Lemma 1.** We assume to deal with finite difference discretization in space and Euler explicit time discretization. Then the time error estimate for the equation (1) is given as:

$$\Delta t_{Adv} \le \frac{\Delta x}{3\nu(\Delta t_{Adv})},\tag{18}$$

$$v(t) = \|\mathbf{v}(t)\| = \left(v_n - \frac{vu_n}{\mu \dot{u}_n} \|E\|\right) \exp\left(-\frac{\dot{u}_n}{u_n}t\right) + \frac{vu_n}{\mu \dot{u}_n} \|E\|,$$
(19)

$$\Delta t_{Diff} \le \frac{\Delta x^2}{6D},\tag{20}$$

$$\Delta t_{\max} = \min(\Delta t_{Ad\nu}, \Delta t_{Diff}); \tag{21}$$

where  $\|\cdot\|$  is the Euclidian norm for the vectors and equation (18) is a nonlinear equation solved with Newton's method.

# Proof.

$$\frac{u_i^{n+1} - u_i^n}{\Delta t} = 3 \|\mathbf{v}\| \frac{u_{i+1}^n - u_i^n}{\Delta x} + 3D \frac{u_{i+1}^n - 2u_i^n + u_{i-1}^n}{\Delta x^2}$$
(22)

where *i* are the spatial grid points and **v** is given analytically in equation (11). We obtain the stability criterion for a stable discretization scheme:

$$u_{i}^{n+1} \leq \left(1 - 3\frac{\|\mathbf{v}\|\Delta t}{\Delta x} - 6\frac{D\Delta t}{\Delta x^{2}}\right)u_{i}^{n} + 3\frac{\|\mathbf{v}\|\Delta t}{\Delta x}u_{i+1}^{n} + 3\frac{D\Delta t}{\Delta x^{2}}(u_{i+1}^{n} + u_{i-1}^{n})$$
(23)

where the CFL condition is given as:

$$\left(1 - 3\frac{\|\mathbf{v}\|\Delta t}{\Delta x} - 6\frac{D\Delta t}{\Delta x^2}\right) > 0$$
(24)

we deal with the stronger restriction:

$$1 - 3\frac{\|\mathbf{v}\|\Delta t}{\Delta x} > 0,\tag{25}$$

$$1 - 6\frac{D\Delta t}{\Delta x^2} > 0. \tag{26}$$

Then the CLF conditions are given as

$$\Delta t_{Adv} \le \frac{\Delta x}{3\nu(\Delta t_{Adv})},\tag{27}$$

$$v(t) = \|\mathbf{v}(t)\| = \left(v_n - \frac{vu_n}{\mu \dot{u}_n} \|E\|\right) \exp\left(-\frac{\dot{u}_n}{u_n}t\right) + \frac{vu_n}{\mu \dot{u}_n} \|E\|,$$
(28)

$$\Delta t_{Diff} \leq = \frac{\Delta x^2}{6D},\tag{29}$$

$$\Delta t_{\max} = \min(\Delta t_{Adv}, \Delta t_{Diff}); \tag{30}$$

where  $\|\cdot\|$  is the Euclidian norm for the vectors and the analytical solution of the velocity is given as:

$$3\Delta t_{Adv} \left( v_n - \frac{vu_n}{\mu \dot{u}_n} \|E\| \right) \exp\left( -\frac{\dot{u}_n}{u_n} \Delta t_{Adv} \right) + 3\Delta t_{Adv} \frac{vu_n}{\mu \dot{u}_n} \|E\| \le \Delta x, \quad (31)$$

$$F(\Delta t_{Adv}) - \Delta x \le 0 \tag{32}$$

and equation (32) is a real-valued function, where the roots are solved by Newton's method.  $\hfill \Box$ 

# 4. Splitting methods to couple Electrostatic and Convection Diffusion equation

We concentrate on the splitting methods, which can be classified as classical and iterative splitting methods.

We propose iterative splitting methods by discussing the additive iterative splitting methods, see [4] and [10].

We consider the following the nonlinear problem

$$\frac{\partial u}{\partial t} = A_1(\mathbf{v})u + B(\mathbf{v})u,\tag{33}$$

$$\frac{\partial \mathbf{v}}{\partial t} = A_2 \left( \frac{\partial u}{\partial t}, u \right) \mathbf{v} + \mathbf{f},\tag{34}$$

where the initial conditions are  $u^n = u(t^n)$ ,  $\mathbf{v}^n = \mathbf{v}(t^n)$ . The operators  $A_1$  and  $A_2$  are spatially discretized operators, e.g. they correspond in space to the discretized convection and diffusion operators (matrices). Hence, they can be considered as bounded operators with a sufficient large spatial step  $\Delta x > 0$ .

113

# 4.1. Iterative splitting methods

The following algorithm is based on the iteration with fixed splitting discretization step size  $\tau$ . On the time interval  $[t^n, t^{n+1}]$  we solve the following subproblems consecutively for i = 1, 3, ..., 2m + 1, cf. [4] and [10].

$$\frac{\partial u_{i}(t)}{\partial t} = A_{1}(\alpha \mathbf{v}_{i-1}(t) + (1-\alpha)\mathbf{v}_{i-1}(t^{n}))u_{i}(t) \qquad (35)$$

$$+ B(\alpha \mathbf{v}_{i-1}(t) + (1-\alpha)\mathbf{v}_{i-1}(t^{n}))u_{i-1}(t), \qquad (35)$$
with  $u_{i}(t^{n}) = u^{n}, \ \mathbf{v}_{i-1}(t^{n}) = \mathbf{v}^{n}, \qquad (36)$ 
with  $u_{i}(t^{n}) = u^{n}, \ \mathbf{v}_{i}(t^{n}) = \mathbf{v}^{n}, \qquad (36)$ 
with  $u_{i}(t^{n}) = u^{n}, \ \mathbf{v}_{i}(t^{n}) = \mathbf{v}^{n}, \qquad (36)$ 

where  $u_0 \equiv u^n$ ,  $\mathbf{v}_0 \equiv \mathbf{v}^n$  are the known split approximation at time level  $t = t^n$ . The split approximation at time level  $t = t^{n+1}$  is defined as  $u^{n+1} = u_i(t^{n+1})$ ,  $\mathbf{v}^{n+1} \equiv \mathbf{v}_i(t^{n+1})$ .

While  $\alpha \in [0, 1]$  is the weighting factor and  $\alpha = 0$  is purely explicit and we are done in i = 1,  $\alpha = 1$  is pure implicit and we have approximate the last solutions.

Remark 3. The stop criterion of the iterative splitting scheme is given as:

- We stop after a fixed number of iterative steps, e.g. i = 3
- or we stop after an error bound is reached, we assume that there exists an *i* with:

$$\max\{\|u_{i}(t) - u_{i-1}(t)\|, \|v_{i}(t) - v_{i-1}(t)\|\} \le err,$$
(37)

where  $\|\cdot\|$  is a given vector norm, e.g. Euclidian norm and  $err \in \mathbb{R}^+$  is a given error bound, e.g.  $err = 10^{-4}$ .

## 5. Error Analysis: Coupling Methods

For a simpler notation, we define  $c = (u, \mathbf{v})^t$  as a new variable, including the concentration and velocity field.

Based on this, we deal with nonlinear differential equations of the following type:

$$\frac{dc}{dt} = A(c(t))c(t) + B(c(t))c(t), \text{ with } c(t^n) = c^n,$$
(38)

where  $c = (u, \mathbf{v})^t$ , with  $\mathbf{v}$  is the velocity field (including the electrostatic field in a analytical version) and u is the concentration of the species.

The main idea is to bound the operators A(c(t)) and B(c(t)) in the discretized equation to satisfy a stable method.

A first idea is the fix-point scheme, that is discussed in the following subsection.

## 5.1. Consistency and stability analysis

In the following, we discuss the iterative operator-splitting method as a fixedpoint iteration method to linearize the operators.

We apply for the nonlinear differential equation (38) the following iterative scheme:

$$\partial_t c_i = A(c_{i-1})c_i + B(c_{i-1})c_{i-1}, \text{ with } c_i(x, t^n) = c^n,$$
(39)

$$\partial_t c_{i+1} = A(c_{i-1})c_i + B(c_{i-1})c_{i+1}, \text{ with } c_{i+1}(x, t^n) = c^n,$$
(40)

where the time-step is  $\tau = t^{n+1} - t^n$ . The iterations are i = 1, 3, ..., 2m + 1.  $c_0(x, t) = c^n$  is the initial solution, where we assume that the solution  $c^{n+1}$  is near  $c^n$ , or  $c_0(x, t) \equiv 0$ . Thus we have to solve the local fixed-point problem.  $c^n$  is the known split approximation at time-level  $t = t^n$ .

The split approximation at time-level  $t = t^{n+1}$  is defined as  $c^{n+1} = c_{2m+2}(x, t^{n+1})$ . We assume that the operators  $A(c_{i-1}(x, t^{n+1}))$ ,  $B(c_{i-1}(x, t^{n+1}))$  are constant for i = 1, 3, ..., 2m + 1. Here the linearization is done with respect to the iterations such that  $A(c_{i-1})$ ,  $B(c_{i-1})$  are at least non-dependent operators in the iterative equations, and we can apply the linear theory.

## **Assumption 1.** We have the following assumptions to the fix-point scheme:

- For the first equation (39), we have  $A(c_{i-1}(x,t)) \approx A(c_i(x,t))$ , for small t.
- For the second equation (40), we have  $B(c_{i-1}(x,t)) \approx B(c_{i+1}(x,t))$ , for small t.
- We have  $||A(c_{i-1}(x, t^{n+1}))c_i(x, t^{n+1}) A(c(x, t^{n+1}))c(x, t^{n+1})|| \le \epsilon$ , for sufficient iterations  $i \in \{1, 3, ..., 2m + 1\}$ .

**Remark 4.** The linearization with the fixed-point scheme can be used for smooth or weak nonlinear operators, otherwise we lose the convergence behavior, while we did not converge to the local fixed point, see [10].

Next, we demonstrate the error analysis for the linear and nonlinear decomposition methods. In this section we designate as  $e_i(t) := c(t) - c_i(t)$  the error between the exact solution and the approximated solution after *i* iterations. Here we discuss the linearization techniques and their approximations.

Theorem 1. Let us consider the following problem

$$\begin{aligned} \partial_t c(t) &= A(c(t))c(t) + B(c(t))c(t), \quad 0 < t \le T , \\ c(0) &= c_0 , \end{aligned}$$

where A, B are nonlinear differentiable bounded operators A, B in a Banach space X. Linearizing the nonlinear operators yields the linearized equation

$$\partial_t c(t) = \widehat{A}c(t) + \widehat{B}c(t) + R(c_{\widetilde{i}})c_{\widetilde{i}}, \quad 0 < t \le T ,$$
  
$$\widetilde{A} = A(c_{\widetilde{i}}) + \frac{\partial A(c_{\widetilde{i}})}{\partial c}c_{\widetilde{i}}, \quad \widetilde{B} = B(c_{\widetilde{i}}) + \frac{\partial B(c_{\widetilde{i}})}{\partial c}c_{\widetilde{i}},$$

115 Iterative Operator Splitting Method for Coupled Problems: Transport and Electric Fields

$$R(c_{\tilde{i}}) = \frac{\partial A(c_{\tilde{i}})}{\partial c} c_{\tilde{i}} + \frac{\partial B(c_{\tilde{i}})}{\partial c} c_{\tilde{i}}, \qquad (41)$$
$$c(0) = c_0,$$

where  $\widetilde{A}, \widetilde{B}, \widetilde{A} + \widetilde{B} : \mathbf{X} \to \mathbf{X}$  are given, linear bounded operators being generators of the  $C_0$ -semigroup and  $c_0 \in \mathbf{X}$  is a given element. The linearization is of the form  $A(c)c \approx A(c_{\tilde{i}})c_{\tilde{i}} + (\frac{\partial A(c_{\tilde{i}})}{\partial c}c_{\tilde{i}})(c - c_{\tilde{i}})$  where  $c_{\tilde{i}} \in \mathbf{X}$  is a linearized solution, we further assume  $\left(\frac{\partial A(c_i)}{\partial c}\right)c_i$  is a constant Jacobian matrix. We assume that the iteration process (39)-(40) is convergent and the convergence is

of second order.

It holds

$$\|e_i\| = K\tau_n \|e_{i-1}\| + \mathcal{O}(\tau_n^2), \tag{42}$$

where K is an estimation of the residual  $||R(\tilde{c})|| \leq R_{\max} \in \mathbb{R}^+$  for all  $\tilde{c} \in \mathbf{X}$  and  $\|\widetilde{B}\| \leq \widetilde{K}.$ 

One could also obtain the result with Lipschitz-constants. We now prove the argument using the semi-group theory.

**Proof.** Let us consider the iteration (39)-(40) in the sub-interval  $[t^n, t^{n+1}]$ . The linearized splitting method is given as :

$$\frac{\partial c_i(t)}{\partial t} = \widetilde{A}c_i(t) + \widetilde{B}c_{i-1}(t) + R(c_{i-1})c_{i-1}(t),$$
(43)

with 
$$c_i(t^n) = c^n$$
 (44)

$$c_{0}(t^{n}) = c^{n}, c_{-1} = 0,$$
  

$$\frac{\partial c_{i+1}(t)}{\partial t} = \widetilde{A}c_{i}(t) + \widetilde{B}c_{i+1}(t) + R(c_{i-1})c_{i-1}(t),$$
(45)  
with  $c_{i+1}(t^{n}) = c^{n},$ 

where  $c^n$  is the known split approximation at the time level  $t = t^n$ . We solve the subproblems consecutively for i = 0, 2, ..., 2m.

For the error function  $e_i(t) = c(t) - c_i(t)$  we have the relations

$$\partial_t e_i(t) = \widetilde{A}(e_i(t)) + \widetilde{B}(e_{i-1}(t)) + R(e_{i-1})e_{i-1}(t), \quad t \in (t^n, t^{n+1}],$$

$$e_i(t^n) = 0, \quad (46)$$

and

$$\partial_t e_{i+1}(t) = \widetilde{A}(e_i(t)) + \widetilde{B}(e_{i+1}(t)) + R(e_{i-1})e_{i-1}(t), \quad t \in (t^n, t^{n+1}],$$

$$e_{i+1}(t^n) = 0, \quad (47)$$

for  $m = 0, 2, 4, \dots$ , with  $e_0(0) = 0$  and  $e_{-1}(t) = c(t)$  and  $= A(e_{i-1}) + - \partial A(e_{i-1})$ à :

$$= A(e_{i-1}) + \frac{\partial A(e_{i-1})}{\partial c}e_{i-1},$$

$$\widetilde{B} = B(e_{i-1}) + \frac{\partial B(e_{i-1})}{\partial c} e_{i-1},$$
$$R(e_{i-1}) = \frac{\partial A(e_{i-1})}{\partial c} e_{i-1} + \frac{\partial B(e_{i-1})}{\partial c} e_{i-1}$$

In the following we derive the linearized equations. We use the notation  $\mathbf{X}^2$  for the product space  $\mathbf{X} \times \mathbf{X}$  enabled with the norm  $||(u, v)|| = \max\{||u||, ||v||\}$   $(u, v \in \mathbf{X})$ . The elements  $\mathscr{E}_i(t), \mathscr{F}_i(t) \in \mathbf{X}^2$  and the linear operator  $\mathscr{A} : \mathbf{X}^2 \to \mathbf{X}^2$  are defined as follows

$$\mathscr{E}_{i}(t) = \begin{bmatrix} e_{i}(t) \\ e_{i+1}(t) \end{bmatrix}; \quad \mathscr{A} = \begin{bmatrix} \widetilde{A} & 0 \\ \widetilde{A} & \widetilde{B} \end{bmatrix},$$
(48)

$$\mathscr{F}_{i}(t) = \begin{bmatrix} R(e_{i-1})e_{i-1} + \widetilde{B}e_{i-1} \\ R(e_{i-1})e_{i-1} \end{bmatrix}$$
(49)

where have the bounded and linearized operators  $\widetilde{A}$ ,  $\widetilde{B}$  and  $R(e_{i-1})$ .

Using notation (18) and (48), the relations (46)-(47) can be written in the form

$$\partial_t \mathscr{E}_i(t) = \mathscr{A} \mathscr{E}_i(t) + \mathscr{F}_i(t), \quad t \in (t^n, t^{n+1}],$$
  
$$\mathscr{E}_i(t^n) = 0.$$
 (50)

Due to our assumptions that *A* and *B* are bounded and differentiable and that we have a Lipschitzian domain,  $\mathscr{A}$  is a generator of the one-parameter  $C_0$  semigroup  $(\mathscr{A}(t))_{t\geq 0}$ . We also assume the estimate of our term  $\mathscr{F}_i(t)$  with the growth conditions.

We can estimate the right hand side  $\mathscr{F}_i(t)$  with help of Lemma 1 presented after this proof. Hence, using the variations of constants formula, the solution of the abstract Cauchy problem (50) with homogeneous initial condition can be written as (cf. e.g. [2])

$$\mathscr{E}_{i}(t) = \int_{t^{n}}^{t} \exp(\mathscr{A}(t-s))\mathscr{F}_{i}(s)ds, \quad t \in [t^{n}, t^{n+1}].$$
(51)

Hence, using the denotation

$$\|\mathscr{E}_{i}\|_{\infty} = \sup_{t \in [t^{n}, t^{n+1}]} \|\mathscr{E}_{i}(t)\| , \qquad (52)$$

and taking into account Lemma 1, we have

$$\begin{aligned} \|\mathscr{E}_{i}(t)\|_{\infty} &\leq \|\mathscr{F}_{i}\|_{\infty} \int_{t^{n}}^{t} \|\exp(\mathscr{A}(t-s))\| ds \\ &\leq C \|e_{i-1}(t)\| \int_{t^{n}}^{t} \|\exp(\mathscr{A}(t-s))\| ds, \quad t \in [t^{n}, t^{n+1}]. \end{aligned}$$
(53)

Since  $(\mathscr{A}(t))_{t\geq 0}$  is a semigroup, the so called *growth estimate* is

$$\|\exp(\mathscr{A}t)\| \le K \exp(\omega t), \quad t \ge 0,$$
(54)

with some numbers  $K \ge 0$  and  $\omega \in \mathbb{R}$  (see [2]).

Assume that (𝔄(t))<sub>t≥0</sub> is a bounded or exponentially stable semigroup, i.e. that
 (54) holds with some ω ≤ 0. Then obviously the inequality

$$\|\exp(\mathscr{A}t)\| \le K; \quad t \ge 0, \tag{55}$$

holds, and hence from (53), we have

$$\|\mathscr{E}_{i}(t)\|_{\infty} \leq K\tau_{n} \|e_{i-1}(t)\|, \quad t \in (0, \tau_{n}).$$
(56)

Assume that (𝔄(t))<sub>t≥0</sub> has exponential growth with some ω > 0. From (54) we have

$$\|\exp(\mathscr{A}(t-s))\|ds \le K_{\omega}(t), \quad t \in [t^n, t^{n+1}],$$
(57)

where

$$K_{\omega}(t) = \frac{K}{\omega} \left( \exp(\omega(t - t^n)) - 1 \right), \quad t \in [t^n, t^{n+1}],$$
(58)

and hence

$$K_{\omega}(t) \leq \frac{K}{\omega} \left( \exp(\omega \tau_n) - 1 \right) = K \tau_n + \mathcal{O}(\tau_n^2),$$
(59)

where  $\tau_n = t^{n+1} - t^n$ . The estimations (56) and (59) result in

$$\|\mathscr{E}_i\|_{\infty} = K\tau_n \|e_{i-1}\| + \mathscr{O}(\tau_n^2).$$
(60)

Taking into the account the definition of  $\mathscr{E}_i$  and the norm  $\|\cdot\|_{\infty}$ , that results to have the estimation  $\|e_{i+1}\| \leq \|e_i\|$ , we obtain

$$||e_i|| = K\tau_n ||e_{i-1}|| + \mathcal{O}(\tau_n^2),$$

which proves our statement.

**Lemma 2.** The term 
$$\mathscr{F}_i(t)$$
 given by (49) can be estimated as

$$\|\mathscr{F}_{i}(t)\| \le C \|e_{i-1}\|.$$
(61)

where we assume the boundedness of  $R(e_{i-1})$  and  $\tilde{B}$ , see Theorem 1.

**Proof.** We have the norm  $||\mathscr{F}_i(t)|| = \max\{\mathscr{F}_{i_1}(t), \mathscr{F}_{i_2}(t)\}$ . Each term can be bounded as follows.

$$\|\mathscr{F}_{i_{1}}(t)\| \leq \|(R(e_{i-1}(t)) + B)e_{i-1}(t)\|$$

$$\leq (R_{\max} + \widetilde{K})\|e_{i-1}(t)\|, \qquad (62)$$

$$\|\mathscr{F}_{i_{2}}(t)\| \leq \|R(e_{i-1}(t))e_{i-1}(t)\|$$

$$\leq R_{\max} \| e_{i-1}(t) \| \,. \tag{63}$$

where  $R_{\text{max}}$  and  $\tilde{K}$  are constants and defined in Theorem 1.

So we obtain the estimate

$$\|\mathscr{F}_{i}(t)\| \leq C \|e_{i-1}(t)\|,$$
  
where  $C = R_{\max} + \widetilde{K}$ .

# 6. Experiments

In the following experiments we couple transport equations and flow-field equations with embedded electrical fields.

We deal with the following coupled partial differential equations (transport and flow-field equations):

$$\frac{\partial u}{\partial t} = -\mathbf{v} \cdot \nabla u + \nabla \cdot D \nabla u, \tag{64}$$

$$\frac{\partial \mathbf{v}}{\partial t} = -\frac{\frac{\partial u}{\partial t}}{u} \mathbf{v} + \frac{v}{\mu} \mathbf{E},\tag{65}$$

$$u(\mathbf{x}, \mathbf{t_0}) = u_0(\mathbf{x}),\tag{66}$$

$$\mathbf{v}(\mathbf{x}, \mathbf{t}_0) = \mathbf{v}_0(\mathbf{x}),\tag{67}$$

where we have Neumann boundary conditions.

We deal with several methods and have the following general setting. Let  $\Omega = [0,1] \times [0,1] \times [0,1]$ , the unit cube. There we set up the initial concentration

$$u_{t_0}(\mathbf{x}) = 2 \exp\left(\frac{-(\mathbf{x} - \mathbf{a})^2}{0.02}\right) \quad \forall \ \mathbf{x} \in \Omega,$$
(68)

with 
$$\mathbf{a} = (0.5, 0.5, 0.5)^T$$
, (69)

which is just the analytical solution

$$u_a(\mathbf{x},t) = \frac{1}{t} \exp\left(\frac{-(\mathbf{x} - \mathbf{v}t)^2}{4Dt}\right),\tag{70}$$

with  $\mathbf{v} = \mathbf{1}$  and D = 0.01 at  $t = t_0 = 0.5$  on  $\Omega$ .

During the following experiments we will set  $\mathbf{v} = \mathbf{0}$  and consider an equidistant lattice of  $N^3$  points ( $\Delta x = \Delta y = \Delta z = \Delta = \frac{1}{N-1}$ ). We set  $\Delta_0 = \frac{1}{60}$ ,  $\Delta t_0 = \frac{1}{4}\Delta_0$  and  $t_{end} = 1.5041\overline{6}$  ( $t_{end} = t_0 + 241 \cdot \Delta t_0$ ).

To calculate the  $L_2$ -error we will use a reference solution which is generated with Kutta's fourth order method where N = 241 so that  $\Delta = \frac{1}{240}$  and  $\Delta t = \frac{1}{48}\Delta$ .

In the following tabular (Kutta fourth order) all values have the dimension  $1 \cdot 10^{-3}$ .

	$\Delta t_0$	$\frac{1}{2}\Delta t_0$	$\frac{1}{3}\Delta t_0$	$\frac{1}{4}\Delta t_0$	$\frac{1}{5}\Delta t_0$	$\frac{1}{6}\Delta t_0$	$\frac{1}{7}\Delta t_0$	$\frac{1}{8}\Delta t_0$	$\frac{1}{9}\Delta t_0$	$\frac{1}{10}\Delta t_0$	$\frac{1}{11}\Delta t_0$	$\frac{1}{12}\Delta t_0$
$\Delta_0$	0.9195	0.9600	0.9735	0.9803	0.9843	0.9870	0.9889	0.9904	0.9915	0.9924	0.9931	0.9938
$\frac{1}{2}\Delta_0$	$\infty$	$\infty$	0.3427	0.3498	0.3540	0.3568	0.3589	0.3604	0.3615	0.3625	0.3633	0.3639
$\frac{1}{3}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	0.1179	0.1200	0.1215	0.1227	0.1236	0.1244	0.1251
$\frac{1}{4}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	0

The last value is zero because this was the reference solution. The result is graphically shown in Figure 1.

Iterative Operator Splitting Method for Coupled Problems: Transport and Electric Fields

119




Figure 1. Maximum error Kutta's fourth

In the following tabular (Heun third order) all values have the dimension  $1\cdot 10^{-3}.$ 

		$\Delta t_0$	$\frac{1}{2}\Delta t_0$	$\frac{1}{3}\Delta t_0$	$\frac{1}{4}\Delta t_0$	$\frac{1}{5}\Delta t_0$	$\frac{1}{6}\Delta t_0$	$\frac{1}{7}\Delta t_0$	$\frac{1}{8}\Delta t_0$	$\frac{1}{9}\Delta t_0$	$\frac{1}{10}\Delta t_0$	$\frac{1}{11}\Delta t_0$	$\frac{1}{12}\Delta t_0$
Δ	•0	0.9195	0.9600	0.9735	0.9803	0.9843	0.9870	0.9889	0.9904	0.9915	0.9924	0.9931	0.9938
$\frac{1}{2}$	$\Delta_0$	$\infty$	œ	0.3427	0.3498	0.3540	0.3568	0.3589	0.3604	0.3615	0.3625	0.3633	0.3639
$\frac{1}{3}$	$\Delta_0$	$\infty$	œ	$\infty$	$\infty$	$\infty$	$\infty$	0.1200	0.1215	0.1227	0.1236	0.1244	0.1251
$\frac{1}{4}$	$\Delta_0$	$\infty$	~	∞	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	8	$\infty$	$\infty$	$8 \cdot 10^{-9}$

The result is graphically shown in Figure 2.




Figure 2. Maximum error Heun's third

In the following tabular (Adam-Bashforth second order) all values have the dimension  $1\cdot 10^{-3}.$ 

	$\Delta t_0$	$\frac{1}{2}\Delta t_0$	$\frac{1}{3}\Delta t_0$	$\frac{1}{4}\Delta t_0$	$\frac{1}{5}\Delta t_0$	$\frac{1}{6}\Delta t_0$	$\frac{1}{7}\Delta t_0$	$\frac{1}{8}\Delta t_0$	$\frac{1}{9}\Delta t_0$	$\tfrac{1}{10}\Delta t_0$	$\frac{1}{11}\Delta t_0$	$\frac{1}{12}\Delta t_0$
$\Delta_0$	$\infty$	0.9599	0.9735	0.9802	0.9843	0.9870	0.9889	0.9904	0.9915	0.9924	0.9931	0.9938
$\frac{1}{2}\Delta_0$	$\infty$	$\infty$	~	~	$\infty$	$\infty$	$\infty$	0.3604	0.3615	0.3625	0.3632	0.3639
$\frac{1}{3}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
$\frac{1}{4}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$

The result is graphically shown in Figure 3.




Figure 3. Maximum error Adam-Bashforth second

In the following tabular (Adam-Bashforth third order) all values have the dimension  $1\cdot 10^{-3}.$ 

	$\Delta t_0$	$\frac{1}{2}\Delta t_0$	$\frac{1}{3}\Delta t_0$	$\frac{1}{4}\Delta t_0$	$\frac{1}{5}\Delta t_0$	$\frac{1}{6}\Delta t_0$	$\frac{1}{7}\Delta t_0$	$\frac{1}{8}\Delta t_0$	$\frac{1}{9}\Delta t_0$	$\frac{1}{10}\Delta t_0$	$\frac{1}{11}\Delta t_0$	$\frac{1}{12}\Delta t_0$
$\Delta_0$	$\infty$	$\infty$	$\infty$	0.9803	0.9843	0.9870	0.9889	0.9904	0.9915	0.9924	0.9931	0.9938
$\frac{1}{2}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	∞
$\frac{1}{3}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	∞
$\frac{1}{4}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	∞

The result is graphically shown in Figure 4.




Figure 4. Maximum error Adam-Bashforth third

121

In the following tabular (Adam-Bashforth fourth order) all values have the dimension  $1\cdot 10^{-3}.$ 

	$\Delta t_0$	$\frac{1}{2}\Delta t_0$	$\frac{1}{3}\Delta t_0$	$\frac{1}{4}\Delta t_0$	$\frac{1}{5}\Delta t_0$	$\frac{1}{6}\Delta t_0$	$\frac{1}{7}\Delta t_0$	$\frac{1}{8}\Delta t_0$	$\frac{1}{9}\Delta t_0$	$\frac{1}{10}\Delta t_0$	$\frac{1}{11}\Delta t_0$	$\frac{1}{12}\Delta t_0$
$\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	~	0.9870	0.9889	0.9904	0.9915	0.9924	0.9931	0.9938
$\frac{1}{2}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
$\frac{1}{3}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
$\frac{1}{4}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$

The result is graphically shown in Figure 5.




Figure 5. Maximum error Adam-Bashforth fourth

In the following tabular (Adam-Bashforth fifth order) all values have the dimension  $1\cdot 10^{-3}.$ 

	$\Delta t_0$	$\frac{1}{2}\Delta t_0$	$\frac{1}{3}\Delta t_0$	$\frac{1}{4}\Delta t_0$	$\frac{1}{5}\Delta t_0$	$\frac{1}{6}\Delta t_0$	$\frac{1}{7}\Delta t_0$	$\frac{1}{8}\Delta t_0$	$\frac{1}{9}\Delta t_0$	$\frac{1}{10}\Delta t_0$	$\frac{1}{11}\Delta t_0$	$\frac{1}{12}\Delta t_0$
$\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	0.9931	0.9938
$\frac{1}{2}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	∞
$\frac{1}{3}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$
$\frac{1}{4}\Delta_0$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$	$\infty$

The result is graphically shown in Figure 6.




Figure 6. Maximum error Adam-Bashforth fifth

This results show that the quality of all four methods is much more restricted by the accuracy in space than in time.

**Remark 5.** We receive convergent results in time and space for the Adam-Bashforth and iterative splitting solver. The results can be improved by using higher order Adam-Bashforth methods and more refined grids.

# 7. Conclusion

We discussed iterative splitting schemes for nonlinear coupled partial differential equations. The numerical analysis is presented for nonlinear and spatial discretized equations and we obtain higher order results with more iterative steps. With explicit discretization schemes as Adam-Bashforth methods, we can accelerate our solver schemes, while we skip costly implicit methods. A priori error estimates allow to optimize the time steps. In future we are taken into account a framework to couple partial differential equations based on fix-point and iterative schemes.

# Appendix A.

# A.1. Explicit Time-Integration Methods

To have fast methods, we consider explicit time-integration methods for the coupled equations.

We consider Adam-Bashforth (AB) and Runge-Kutta (RK) methods.

While the time steps *AB*1 is  $\Delta t \approx \frac{1}{\sqrt{50}} \Delta x$  and *AB*2 is  $\Delta t \approx \frac{1}{\sqrt{200}} \Delta x$ , we apply the RK schemes with  $\Delta t \approx \frac{1}{\sqrt{7}} \Delta x$ .

A.1.1. Adam-Bashforth methods.

$$y_{n+1} = y_n + h \sum_{j=0}^{3} b_j f(t_{n-j}, y_{n-j}),$$
(71)

$$b_{j} = \frac{(-1)^{j}}{j!(s-j)!} \int_{0}^{1} \prod_{i=0, i \neq j}^{s} (u+i) \, du, \quad j = 0, \dots, s.$$
(72)

We consider here

s = 2 (second order)

$$y_{n+1} = y_n + h\left(\frac{3}{2}f(t_n, y_n) - \frac{1}{2}f(t_{n-1}, y_{n-1})\right),$$
(73)

s = 3 (third order)

$$y_{n+1} = y_n + h \left( \frac{23}{12} f(t_n, y_n) - \frac{16}{12} f(t_{n-1}, y_{n-1}) + \frac{5}{12} f(t_{n-2}, y_{n-2}) \right), \quad (74)$$

$$s = 4$$
 (fourth order)

$$y_{n+1} = y_n + h \left( \frac{55}{24} f(t_n, y_n) - \frac{59}{24} f(t_{n-1}, y_{n-1}) + \frac{37}{24} f(t_{n-2}, y_{n-2}) - \frac{3}{8} f(t_n - 3, y_n - 3) \right),$$
(75)

and s = 5 (fifth order)

$$y_{n+1} = y_n + h \left( \frac{1901}{720} f(t_n, y_n) - \frac{1387}{360} f(t_{n-1}, y_{n-1}) + \frac{109}{30} f(t_{n-2}, y_{n-2}) - \frac{637}{360} f(t_{n-3}, y_{n-3}) + \frac{251}{720} f(t_n - 4, y_n - 4) \right).$$
(76)

# A.1.2. Explicit Runge-Kutta methods.

In general a s-stage Runge-Kutta method can be written in the following way:

$$y_{n+1} = y_n + h \sum_{j=1}^{s} b_j k_j$$
(77)

where

$$k_{j} = f\left(t_{n} + hc_{j}, y_{n} + h\sum_{l=1}^{s} a_{jl}k_{l}\right).$$
(78)

We will take into account the following two: *Heun's third-order* 

and

Kutta's classical fourth-order

# A.2. Matrix Exponential Methods

Another way of computing fast explicit schemes of ODE systems of first order are matrix exponentials.

We deal with:

$$\frac{dy}{dt} = Ay, \ y(0) = y_0,$$
 (81)

where we assume A = D + N, D is the diagonal part and N is the nilpotent part of the matrix A.

We assume also [D, N] = 0 and we have the solution:

$$y(t) = \exp(Dt)\exp(Nt)y_0,$$
(82)

where exp(Dt) can be computed just exponentiating every entry on the main diagonal and

$$\exp(Nt) \approx I + N \ t + N^2 \ \frac{t^2}{2} + N^3 \ \frac{t^3}{3},$$
(83)

where *N* is the nilpotent matrix and  $N \cdot N$  is only a shift of the to the next higher upper or lower diagonal.

## References

- [1] B. Chapman, *Glow Discharge Processes. Sputering and Plasma Etching*, 1st edition, John Wiley & Sons, Inc., 1980.
- [2] K.-J. Engel and R. Nagel, One-Parameter Semigroups for Linear Evolution Equations, Springer, New York, 2000.
- [3] I. Farago, Splitting methods for abstract Cauchy problems. Lect. Notes Comp. Sci. 3401, Springer, Berlin, 2005, pp. 35–45
- [4] I. Farago and J. Geiser, Iterative operator-splitting methods for linear problems, *International Journal of Computational Science and Engineering* **3**(4) (2007), 255–263.
- [5] J. Geiser, Numerical simulation of a model for transport and reaction of radionuclides, in *Proceedings of the Large Scale Scientific Computations of Engineering and Environmental Problems*, Sozopol, Bulgaria, 2001.
- [6] J. Geiser, Gekoppelte Diskretisierungsverfahren f r Systeme von Konvektions-Dispersions-Diffusions-Reaktionsgleichungen, Doktor-Arbeit, Universit t Heidelberg, 2003.
- [7] J. Geiser, R<sup>3</sup>T: Radioactive-Retardation-Reaction-Transport-Program for the simulation of radioactive waste disposals, in *Proceedings: Computing, Communications and Control Technologies: CCCT 2004*, The University of Texas at Austin and The International Institute of Informatics and Systemics (IIIS) 2004, to appear.
- [8] J. Geiser, Iterative operator-splitting methods with higher order time-integration methods and applications for parabolic partial differential equations, *Journal of Computational and Applied Mathematics* **217**(2008), 227–242.
- [9] J. Geiser, Decomposition Methods for Differential Equations: Theory and Applications, Chapman & Hall/CRC Press, Numerical Analysis and Scientific Computing, (F. Magoules and Ch.-H. Lai, editors), 2009.
- [10] J. Kanney, C. Miller, and C. Kelley, Convergence of iterative split-operator approaches for approximating nonlinear reactive transport problems, *Advances in Water Resources* 26(2003), 247–261.
- [11] R.J. LeVeque, *Finite Volume Methods for Hyperbolic Problems*, Cambridge Texts in Applied Mathematics, Cambridge University Press, 2002.
- [12] M.A. Lieberman and A.J. Lichtenberg, Principle of Plasma Discharges and Materials Processing, 2nd edition, Wiley-Interscience, John Wiley & Sons, Inc Publication, 2005.
- [13] G.I Marchuk, Some applications of splitting-up methods to the solution of problems in mathematical physics, *Aplikace Matematiky* 1(1968), 103–132.
- [14] N. Morosoff, Plasma Deposition, Treatment and Etching of Polymers, 1st edition, R.d'Agostino ed., Acad. Press, 1990.

- [15] M. Ohring, Materials Science of Thin Films, 2nd edition, Academic Press, San Diego, New York, Boston, London, 2002.
- [16] G. Strang, On the construction and comparision of difference schemes, SIAM J. Numer. Anal., 5(1968), 506–517.
- [17] E. Zeidler, Nonlinear Functional Analysis and its Applications. II/B Nonlinear Montone Operator, Springer-Verlag, Berlin — Heidelberg — New York, 1990.

J rgen Geiser, Department of Mathematics, Humboldt-Universit t zu Berlin, Unter den Linden 6, D-10099 Berlin, Germany. E-mail: geiser@mathematik.hu-berlin.de

Received April 12, 2011 Accepted June 17, 2011